

## Linear Three Phase Brushless Ironless Motor

<b>FORCER LBF-032-048-321-01</b>			
<b>PERFORMANCE</b>			
Intermittent Force @ 10% Duty Cycle	108.0	lb	
	480.6	N	
Continuous Force @ 25 °C	34.0	lb	
	151.3	N	
Continuous Force @ Tmax	29.0	lb	
	129.0	N	
Continuous Power	126	W	
Motor Constant	3.0	lb/ W <sup>0.5</sup>	
	13.5	N/ W <sup>0.5</sup>	
<b>ELECTRICAL SPECIFICATIONS</b>			
	Wye	Delta	
Peak Current @ 10% Duty Cycle	6.2	10.7	A
Continuous Current @ Tmax	1.7	2.9	A
Force Constant	17.4	10.1	lb/A
	77.4	44.5	N/A
Back EMF	2.0	1.1	V/in/s
	77.4	44.5	V/m/s
Resistance @ 25 °C	33.2	11.1	Ohm
Inductance @ 1 KHz	11.5	3.8	mH



<b>MECHANICAL SPECIFICATIONS</b>		
Coil Assembly Mass	2.03	lb
	0.92	N
Magnetic Cogging Force	0	lb
	0	N
Magnetic Cogging Force	110	°C
Electrical Cycle Length	1.6	in
	40.6	mm
<b>ELECTRICAL SPECIFICATIONS</b>		
Thermal Time Constant	3	min
Thermal Resistance	2.24	°C/W

<b>MAGNETIC TRACK</b> <b>LBM-032-057-XXX-01</b>		
<b>DIMENSIONS</b>		
Width	1.25	in
	32	mm
Height	2.25	in
	57	mm
Length		
LBM-032-057-121-01	4.75	in
	121	mm
LBM-032-057-243-01	9.55	in
	243	mm
LBM-032-057-365-01	14.35	in
	365	mm
LBM-032-057-608-01	23.95	in
	608	mm
Mass		
All Models	0.58	lb/in
	10.3	Kg/m

xxx denotes the track length in mm. Available options are 121, 243, 365 and 608 mm.

Specifications are subject to change without notice.



**MotiCont**  
 6901 Woodley Avenue  
 Van Nuys, California 91406, USA  
[www.MotiCont.com](http://www.MotiCont.com)

**Phone (888) 785-1804**  
 +1 (818) 785-1800  
 FAX +1 (818) 785-5713  
[MotiCont@MotiCont.com](mailto:MotiCont@MotiCont.com)

